

FLOW-SYNC®

Sensor: **Flow**

KEY BENEFITS

- Simple-insertion flow sensor for metering and reacting to real-time flow conditions
- Provides station-level flow monitoring for reaction to high- or low-flow conditions, helping to protect against flood damage and erosion
- Compatible with Hunter ACC2 and legacy ACC and I-Core® Controllers, as well as ICD-SEN Sensor Decoders, for installation flexibility in a variety of settings
- Easy connection up to 1,000' from controller or sensor decoder
- Sensor is pre-calibrated for K-factor and Offset based on pipe size, allowing for quick setup and programming within the controller

OPERATING SPECIFICATIONS

- Recommended pressure range: 0 to 220 PSI
- Pressure loss: < 1 PSI
- Sensor wiring: 2 x direct burial, 18 AWG or greater, color-coded or marked for polarity, up to 1,000' from the controller
- Warranty period: 5 years

USER-INSTALLED OPTIONS

- FCT tee fittings for pipe installation




Impeller-type flow sensor, requires FCT fitting for pipe installation (order separately)

Compatible with:



**ACC2
Controllers**



**ICD-SEN
Decoder**



**Waterproof
Splice Kit**

FLOW-SYNC

Model	Description
HFS	Hunter Flow-Sync Sensor for use with ACC2 and legacy ACC and I-Core Controllers; sensor requires FCT fitting for pipe installation

REQUIRED USER-INSTALLED OPTION (SPECIFY SEPARATELY)

Model	Description
FCT-100	1" Schedule 40 sensor receptacle tee
FCT-150	1½" Schedule 40 sensor receptacle tee
FCT-158	1½" Schedule 80 sensor receptacle tee
FCT-200	2" Schedule 40 sensor receptacle tee
FCT-208	2" Schedule 80 sensor receptacle tee
FCT-300	3" Schedule 40 sensor receptacle tee
FCT-308	3" Schedule 80 sensor receptacle tee
FCT-400	4" Schedule 40 sensor receptacle tee

FLOW RANGE

Pipe Diameter	Operating Range (GPM)	
	Minimum	Suggested Maximum*
1"	2	17
1½"	5	35
2"	10	55
3"	28	120
4"	34	200

Note:

* Good design practice dictates the maximum flow not to exceed 5'/sec. Suggested maximum flow is based upon Class 200 IPS plastic pipe.

SENSORS