

# QUICK COUPLERS

The sturdy red brass and stainless steel construction of Quick Couplers strengthens any project.

## KEY BENEFITS

- 100% interchangeable with major brands
- Red brass and stainless steel construction
- Heavy-duty thermoplastic locking and non-locking covers
- Optional winged stabilization and Acme key connection
- Stainless steel lug on 1" and 1¼" keys
- Spring-loaded covers with stainless steel springs for positive closing and protection of valve's sealing components
- Warranty period: 5 years
- See the SnapLok combo kit



Quick Couplers

## QUICK COUPLER, KEY, AND HOSE SWIVEL CHARTS

Model	Inlet Threads	Slots	Body	Color*	Locking	Key	Swivels
HQ-3-RC	¾"	2	1-piece	Yellow	No	HK-33	HS-0
HQ-33-DRC	¾"	2	2-piece	Yellow	No	HK-33	HS-0
HQ-33-DLRC	¾"	2	2-piece	Yellow	Yes	HK-33	HS-0
HQ-44-RC	1" NPT	1	2-piece	Yellow	No	HK-44	HS-1 or HS-2
HQ-44-LRC	1" NPT	1	2-piece	Yellow	Yes	HK-44	HS-1 or HS-2
HQ-44-RC-AW	1" NPT	Acme	2-piece wing**	Yellow	No	HK-44A	HS-1 or HS-2
HQ-44-LRC-AW	1" NPT	Acme	2-piece wing**	Yellow	Yes	HK-44A	HS-1 or HS-2
HQ-5-RC	1" NPT	1	1-piece	Yellow	No	HK-55	HS-1 or HS-2
HQ-5-LRC	1" NPT	1	1-piece	Yellow	Yes	HK-55	HS-1 or HS-2

### Notes:

\* All locking cover models are available with purple covers for reclaimed water applications.

\*\* Anti-rotation stabilization wings.



HQ-3-RC HQ-5-RC HK-33



HQ-33-DLRC-R HQ-44-LRC HK-44



Non-locking Locking Reclaimed



HQ-44-LRC-AW-R HK-44A



HLK

### Reclaimed Water Option

All locking models have an optional purple cover for sites using reclaimed water.

**QUICK COUPLER – SPECIFICATION BUILDER:** ORDER 1 + 2 + 3

1 Model	2 Cover Options	3 Additional Options
<p><b>HQ-3</b> = ¾" inlet, 1-piece body, 2 slots</p> <p><b>HQ-5</b> = 1" inlet, 1-piece body, 1 slot</p> <p><b>HQ-33-D</b> = ¾" inlet, 2-piece body, 2 slots</p> <p><b>HQ-44</b> = 1" inlet, 2-piece body, 1 slot or Acme key socket</p>	<p><b>RC</b> = Yellow rubber cover</p> <p><b>LRC</b> = Yellow locking rubber cover <i>(Not available for HQ-3 body)</i></p>	<p><b>(blank)</b> = No option</p> <p><b>AW</b> = Acme key with anti-rotation wings <i>(Only available for HQ-44 body)</i></p> <p><b>R</b> = Purple locking cover <i>(reclaimed water ID; only available for LRC models)</i></p>

**Examples:**

**HQ-3-RC** = HQ-3 valve with rubber cover

**HQ-44-LRC** = HQ-44 valve with locking rubber cover

**HQ-44-LRC-R** = HQ-44 valve with locking rubber cover and reclaimed water ID

**HQ-44-LRC-AW-R** = HQ-44 valve, with locking rubber cover, Acme key socket with anti-rotation wings and reclaimed water ID

**KEYS**

Model	Compatible Valve	Compatible Swivel
HK-33 = ¾" valve, ¾" key inlet	HQ-3, HQ-33	HS-0
HK-44 = 1" valve, 1" key inlet	HQ-44	HS-1, HS-2
HK-44A = 1" valve, Acme key inlet	HQ-44-AW	HS-1, HS-2
HK-55 = 1" valve, 1¼" key inlet	HQ-5	HS-1, HS-2

**HS HOSE SWIVELS**

Model	Compatible Key
HS-0 = ¾" inlet, ¾" hose outlet	HK-33
HS-1 = 1" inlet, ¾" hose outlet	HK-44, HK-44A, HK-55
HS-2 = 1" inlet, 1" hose outlet	HK-44, HK-44A, HK-55

**HQ PRESSURE LOSS IN PSI**

Flow (GPM)	HQ-3	HQ-33	HQ-44	HQ-5
5	0.8	1.0		
10	1.8	2.0		
15	4.1	4.3	2.2	
20	7.2	7.6	4.4	1.0
30			11.5	3.0
40				6.3
50				9.2
60				13.0
70				19.8



HS-0

HS-1

HS-2