

LIGHT BAR



DESCRIPTION

The Light Bar is easy to install and its rugged construction and Cerakote® aluminum rail makes it a great fit for high-traffic areas. Light Bars are dimmable with most magnetic transformers and the frosted design offers continuous light. Enhanced ESD (Electro-Static Discharge) protection (IEC-61000-4-2). UL Certified E511083.

Optional light bar shields in Copper or Stainless Steel are available in Small and Medium only.

LIGHT BAR

Use	Areas with Elevation Changes or Dark Sky Requirements Deck, Step, & Hardscape Applications	
Includes	Integrated Light Bar, LightingShrink Professional Crimp, and Heat Shrink Cable Connector	
Integrated Lamp	Small Light Bar - 1.5W, 110 Lumens, 5.125" Length, CRI 85, IP65, 8-15VAC, 5 year warranty	
	2700K	BRI-LB-LED-2700-S
	3000K	BRI-LB-LED-3000-S
	Amber	BRI-LB-LED-AMBER-S
	Medium Light Bar - 2.5W, 200 Lumens, 9.0" Length, CRI 85, IP65, 8-15VAC, 5 year warranty	
	2700K	BRI-LB-LED-2700-M
	3000K	BRI-LB-LED-3000-M
	Amber	BRI-LB-LED-AMBER-M
	Large Light Bar - 4W, 300 Lumens, 12.875" Length, CRI 85, IP65, 8-15VAC, 5 year warranty	
	2700K	BRI-LB-LED-2700-L
	3000K	BRI-LB-LED-3000-L
Accessories	Mounting Bracket	
	Small	BRI-MB-LED-S
	Medium	BRI-MB-LED-M
	Large	BRI-MB-LED-L
	Light Bar Shield	
	Small Copper	LBS-S-C
	Small Stainless	LBS-S-SS
	Medium Copper	LBS-M-C
	Medium Stainless	LBS-M-SS



NEC® Article 411.5 (B): Lighting systems shall be installed not less than 3m (10ft) horizontally from the nearest edge of the water, unless permitted by Article 680.