

PRO-SPRAY®

Meet the strongest, most versatile spinkler body in the industry.

KEY BENEFITS

- Industry's strongest spray body for years of reliable performance
- Co-molded wiper seal made from chemical- and chlorine-resistant materials
- Innovative seal design prevents cap-to-body leaks, even with a loose cap
- Heavy-duty spring for consistent riser retraction
- Check valve option eliminates low-head drainage

ADDITIONAL FEATURES

- Directional flush plug design for cleaner installation
- Interchangeable components for easier servicing, retrofits, and upgrades
- Compatible with all female-threaded nozzles

OPERATING SPECIFICATIONS

- Operational pressure range: 15 to 100 PSI
- Warranty period: 5 years

FACTORY-INSTALLED OPTIONS

- Check valve available for 4", 6", and 12" models (up to 10' of elevation)
- Reclaimed water ID cap

USER-INSTALLED OPTIONS

- Drain check valve (up to 10' of elevation; P/N 437400SP)
- Reclaimed water ID cap (P/N 458520SP)
- Snap-on reclaimed cover (P/N PROS-RC-CAP-SP)
- Shutoff cap (P/N 213600SP)
- Shutoff nozzle (P/N 916400SP)



Pro-Spray Reclaimed

Pro-Spray models include optional factory-installed purple reclaimed caps

PRO-SPRAY - SPECIFICATION BUILDER: ORDER 1 + 2

1 Models	2 Options
PROS-00 = Shrub adapter	(blank) = No option
PROS-02 = 2" pop-up	CV = Factory-installed drain check valve (Pop-up models only)
PROS-03 = 3" pop-up	R = Factory-installed reclaimed body cap (Shrub molded in purple)
PROS-04 = 4" pop-up	
PROS-06 = 6" pop-up (no side inlet)	
PROS-12 = 12" pop-up (no side inlet)	

PRO-SPRAY (SIDE INLET) MODELS

Model

PROS-06-SI = 6" pop-up with side inlet

PROS-12-SI = 12" pop-up with side inlet

Examples:

PROS-04 = 4" pop-up

PROS-06-CV = 6" pop-up, drain check valve

PROS-12-CV-R = 12" pop-up, drain check valve, reclaimed body cap



PROS-00

Retracted height: 1½"
Inlet size: ½"



PROS-02

Retracted height: 4"
Pop-up height: 2"
Exposed diameter: 2¼"
Inlet size: ½"



PROS-03

Retracted height: 5"
Pop-up height: 3"
Exposed diameter: 2¼"
Inlet size: ½"



PROS-04

Retracted height: 5⅞"
Pop-up height: 4"
Exposed diameter: 2¼"
Inlet size: ½"



[A]



[B]

[A] PROS-06-SI

[B] PROS-06

Retracted height: 8¾"
Pop-up height: 6"
Exposed diameter: 2¼"
Inlet size: ½"



[A]



[B]

[A] PROS-12-SI

[B] PROS-12

Retracted height: 16⅞"
Pop-up height: 12"
Exposed diameter: 2¼"
Inlet size: ½"